

Discontinued Parts



	<p>Quarter-Round Extrusion</p> <p>Aluminum 5000 mm long 20.878 lbs</p>	<p>S600</p> <p>S600.01 S600.11</p>
	<p>Shelf Bracket 30°</p> <p>Steel incl. 2 supporting saddles E2600 for wooden shelves, depth 250 mm 0.595 lbs</p>	<p>E2260</p> <p>E2260.21</p>
	<p>Supporting Angle</p> <p>Aluminum incl. positioning peg for wooden shelves, incl. fixing screw M5 Standard accessory for shelf brackets E2205, E2210, E2215, E2220, E2250 and E2260 0.026 lbs</p>	<p>E2600</p> <p>E2600.21</p>
	<p>Supporting Angle</p> <p>Aluminum incl. plastic clamping screw for glass thickness 6-10 mm and fixing screw M5 standard accessory for shelf brackets E2207, E2212, E2217 and E2222 0.029 lbs</p>	<p>E2601</p> <p>E2601.21</p>
	<p>Knuckle Joint 135°</p> <p>Zinc die cast interior corner incl. 2 screws E111/m and 2 setscrews E111/g for mounting 2 quarter-round extrusions S1100/S1105/S1106 0.463 lbs</p>	<p>S1178</p> <p>S1178.39</p>
	<p>Beam Extrusion 50 mm</p> <p>Aluminum 5000 mm long 9.127 lbs</p>	<p>Z4500</p> <p>Z4500.01</p>
	<p>Adjustable Foot</p> <p>Steel for all round extrusion Φ 80 mm 0.615 lbs</p>	<p>M1236</p> <p>M1236.37</p>
	<p>Shelf Support</p> <p>Plastic with steel pin for use with slotted insert rail S1160 and S1162 0.004 lbs</p>	<p>S1161</p> <p>S1161.51</p>